

CORRECTED VERSION

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
29 March 2001 (29.03.2001)


PCT

(10) International Publication Number
WO 01/022720 A3

- (51) International Patent Classification⁷: H04M 7/00 (74) Agent: GROLZ, Edward, W.; Scully, Scott, Murphy & Presser, 400 Garden City Plaza, Garden City, NY 11530 (US).
- (21) International Application Number: PCT/US00/26228
- (22) International Filing Date: 25 September 2000 (25.09.2000) (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW.
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data: 09/405,409 24 September 1999 (24.09.1999) US (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).
- (71) Applicant: MCIWORLD.COM, INC. [US/US]; 515 East Amite Street, Jackson, MS 39201 (US).
- (72) Inventors: GALLANT, John, K.; 1800 Azurite Trail, Plano, TX 75075 (US). DONOVAN, Steven, R.; 704 Forest Bend, Plano, TX 75025 (US).
- Published:
— with international search report

[Continued on next page]

(54) Title: METHOD OF AND SYSTEM FOR PROVIDING INTELLIGENT NETWORK CONTROL SERVICES IN IP TELEPHONY



(57) Abstract: A method and system for providing intelligent network control services in IP telephony, wherein the system includes a location manager (31) and an IP telephony proxy server (23). The location manager includes an interface to a legacy telephony service control entity (29) and the IP telephony proxy server includes an IP interface to the location manager. If the IP telephony proxy server requires intelligent network services, then the IP telephony proxy server sends an IP telephony session initiation request to the called party at the location manager. The location manager uses the information to query the legacy telephony service control entity for routing information. When the location manager (31) receives a routing response from the service control entity, the location manager maps the response to an IP telephony session control message back to the IP telephony proxy server.

WO 01/022720 A3



(88) Date of publication of the international search report:

18 October 2001

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(48) Date of publication of this corrected version:

7 November 2002

(15) Information about Correction:

see PCT Gazette No. 45/2002 of 7 November 2002, Section II

**METHOD OF AND SYSTEM FOR PROVIDING INTELLIGENT NETWORK
CONTROL SERVICES IN IP TELEPHONY**

The present invention relates generally to the field of IP telephony, and more
5 particularly to providing intelligent network control services in IP telephony.

Internet telephony is the real-time delivery of voice, and other multimedia data,
between two or more parties across a network using Internet protocols (IP). Internet
telephony began in the mid-1990s with the introduction of Internet phone software. Internet
phone software is designed to run on a personal computer equipped with a sound card,
10 speakers, microphone, and modem. Software compresses the voice signal and translates it
into IP packets for transmission over the Internet. This basic PC-to-PC internet telephony
works, however, only if both parties are using Internet phone software.

Internet telephony offers the opportunity to design a global multimedia
communications system that may eventually replace the existing circuit switched telephony
15 infrastructure. In a relatively short period of time, Internet telephony has advanced rapidly.
Many software developers now offer PC telephony software.

Internet telephony is session based rather than connection based. Generally, a first
Internet protocol, such as H.323 or Session Initiation Protocol (SIP) is used to establish the
session and negotiate the capabilities for the session, and second Internet protocol, such Real-
20 time Transport Protocol (RTP), is used to transport the actual media across the IP network.

While IP telephony offers benefits to both users and carriers in terms of cost and
variety of media types, there is a substantial installed base of traditional telephones served by
the public switched telephone network (PSTN). Moreover, in addition to its widespread
nature, the PSTN offers a rich set intelligent network services such as "800" number services,
25 Virtual Private Network (VNET) services, call forwarding, and the like. Accordingly, IP
telephony is not likely, anytime soon, to replace the PSTN. However, there is a desire to
integrate the PSTN with IP networks, including the Internet and private intranets. Thus, there

are instances when a call originated by a phone on the PSTN will be required to be carried through an IP based network for eventual delivery to a second phone on the PSTN. There is a further desire to provide all of the intelligent network services that currently exist in the PSTN to IP telephony calls.

5 The present invention provides method of and system for providing intelligent network control services in IP telephony. The system includes a location manager and an IP telephony proxy server. The location manager includes an interface to a legacy telephony service control entity, such as service control point (SCP). The IP telephony proxy server, which may be, for example, an H.323 gatekeeper or a Session Initiation Protocol (SIP) proxy
10 server, includes an IP interface to the location manager.

When the IP telephony proxy server receives a request to initiate an IP telephony session or call to a called party address or number, the IP telephony proxy server determines if it needs intelligent network services in order to route the request to the called party address or number. Examples of sessions requiring intelligent network services are "800" calls and
15 virtual private network (VNET) calls. If the IP telephony proxy server requires intelligent network services, the IP telephony proxy server sends an IP telephony session initiation request to the called party at the location manager. The location manager uses the information received from the IP telephony proxy server to query the legacy telephony service control entity for routing information. When the location manager receives a routing
20 response from the service control entity, the location manager maps the response to an IP telephony session control message back to the IP telephony proxy server.

Fig. 1 is a block diagram of a system according to the present invention.

Fig. 2 is a call flow diagram of processing of a virtual private network (VNET) call according to one embodiment of the present invention.

25 Fig. 3 is a call flow diagram of processing of a virtual private network (VNET) call according to an alternative embodiment of the present invention.

Referring now to the drawings, and first to Fig. 1, a system according to present invention is designated generally by the numeral 11. The system 11 is adapted to provide telephony services between and among subscribers using traditional telephones 13 and Internet telephones 15. The signaling and media for calls according to the present invention are transported at least in part over the Internet, indicated generally at 17.

Traditional telephones 13 are connected to Internet 17 through traditional telephone switching equipment, such as PBXs 19 and IP telephony gateways 21. IP telephony gateways 21 each include a signaling gateway (not shown) and a media gateway (not shown). The signaling gateway provides bidirectional translation between PSTN telephony signaling, such as SS7, messages and IP telephony signaling messages in protocols such as H.323 or Session Initiation Protocol (SIP). Typically, media gateways use one IP signaling protocol or the other, but not both. The media gateway provides bidirectional conversion between time division multiplexed (TDM) signals and IP transport packets in a protocol such as real-time transport protocol (RTP). IP phones 15 may be connected directly to be internet through a local area network or by modem connection through an Internet service provider.

Generally, call signaling and media are transported across Internet 17 between ingress IP telephony gateway 21a and an egress IP telephony gateway 21b. Typically, routing information is supplied by a proxy server, such as a SIP proxy server 23 or an H.323 gatekeeper 25. In the SIP protocol, an invite message is sent from the ingress IP telephony gateway 21a to the address of the called party at the SIP proxy server 23. For normal calls that do not require intelligent network services, the SIP proxy server 23 knows the address of the called party at the egress IP telephony gateway 21b. IP call setup signaling messages are transported back and forth between the IP telephony gateways 21 and the SIP proxy server 23 until the call is setup. In the present invention, the SIP proxy server 23 and the H.323 gatekeeper 25 are combined in a call control entity 27.

The proxy servers 23 and 25 cannot by themselves, handle calls that require intelligent network services. Examples of calls requiring intelligent network services are "800" number calls Virtual Private Network (VNET) calls, local number portable calls, call forwarded calls, and the like. In traditional PSTN telephony, switches consult service control entities, known as service control points (SCPs), for routing information, such as number translation, in order to route calls properly.

The system 11 makes use of a legacy PSTN system service control entity indicated generally at 29, which may be an SCP. The system 11 includes a location manager 31, which provides alias resolution, gateway selection, and mobility management services to the call control entity 27, as well as accessing the service control entity 29 for such services as VNET and local number portability services on behalf of the call control entity 27.

The location manager 31 functions as a SIP redirect server. A redirect server is a server that accepts a SIP request, maps the address into zero or more new addresses and return are these addresses to the client. Unlike a SIP proxy server, a redirect server does not initiate its own SIP requests. Unlike a SIP user agent server, a redirect server does not accept calls. Thus, if a server of the call control entity 27 cannot send a session initiation request to the IP telephony gateway 21, then the server sends a session initiation request to the called party at the location manager 31. The location manager 31 either consults its own database or accesses the legacy service control entity 29 to obtain a new address for the called party. The location manager 31 then returns the new address to the appropriate server of the call control entity 27.

In a preferred embodiment of the present invention, the H.323 gatekeeper 25 is modified to function in the SIP protocol. Thus, the H.323 gatekeeper 25 communicates with H.323 IP telephony gateways and Internet appliances in the H.323 protocol, and with SIP IP telephony gateways, Internet appliances, and the location manger 31 in the SIP protocol.

Referring now to Fig. 2, the PBX 19a sends a setup message 33 to the IP telephony gateway 21a. The IP telephony gateway 21a maps of the setup message 33 into a SIP invite request 35 addressed to the SIP proxy server 23. The SIP proxy server 23 is unable by itself to process setup for a VNET call. Accordingly, the SIP proxy server 23 sends a SIP invite request 37 to the dialed number at the location manager 31.

Upon receipt of the invite request 37, the location manager 31 queries the service control entity 29 with a routing request 39. The service control entity 29 performs a data lookup and responds to the location manager 31 with a routing response 41. The location manager 31 maps response 41 into a SIP temporarily moved response 43 directed back to SIP proxy server 23. As is well-known those skilled in the art, SIP responses are identified by a number, which for the case of the temporarily moved response is 302. The response 43 provides the SIP proxy server 23 with an IP address for the called party at the egress IP telephony gateway 21b. Accordingly, the SIP proxy server 23 sends an invite request 45 to the called party at the egress IP telephony gateway 21b.

Upon receipt of the invite 45, the egress IP telephony gateway 21b sends a setup message 47 to the PBX 19b. When the PBX 19b rings the line of the called party, the PBX 19b sends an alerting message 49 back to the egress IP telephony gateway 21b. The egress IP telephony gateway 21b then sends a SIP 180 ringing message 51 back to the SIP proxy server 23, which in turn sends a SIP 180 ringing response 53 to the ingress IP telephony gateway 21a. The ingress IP telephony gateway 21a then sends an alerting message 55 to the PBX 19a, which provides a ringing tone to the caller party. When the called party answers, PBX 19b sends a connect message 57 to the egress IP telephony gateway 21b. The egress IP telephony gateway 21b in turn sends a SIP 200 OK response 59 to the SIP proxy server 23. The proxy server 23 sends a 200 OK response 61 to the ingress IP telephony gateway 21a. Upon receipt of the response 61, the ingress IP telephony gateway 21a sends a connect message 63 to the PBX 19a and a SIP ACK request 65 to the SIP proxy server 23. The SIP

proxy server 23 sends an ACK request 67 to the egress IP telephony gateway 21b and VNET session is established.

At the conclusion of the VNET session, the called party hangs up and the PBX 19b sends a release message 69 to the egress IP telephony gateway 21b. The egress IP telephony gateway 21b maps release 69 into a SIP BYE request 71 addressed to the calling party at SIP proxy server 23. The SIP proxy server 23 then sends a BYE request 73 to the calling party at the ingress IP telephony gateway 21a. The ingress IP telephony gateway 21a sends a release message 75 to the PBX 19a to terminate the call. The ingress IP telephony gateway 21a also sends an ACK request 77 to the SIP proxy server 23. The SIP proxy server 23 sends an ACK request 79 back to the egress IP gateway 21b. The SIP proxy server 23 also sends a session detail record 81 to an appropriate billing authority.

Referring now to Fig. 3, in which the signaling gateway of the ingress IP telephony gateway 21a uses the H.323 protocol. The PBX 19a sends a setup message 83 to the ingress IP telephony gateway 21a. The ingress IP telephony gateway 21a maps the setup message 83 into an H.323 ARQ message 85 addressed to the H.323 gatekeeper 25. The H.323 gatekeeper 25 responds to message 85 with an H.323 ACF message 87. Upon receipt of message 87, the ingress IP telephony gateway 21a sends an H.323 setup message 89 to gatekeeper 25. The H.323 gatekeeper 25 is unable by itself to process setup for a VNET call. Accordingly, the H.323 gatekeeper 25 sends a SIP invite request 91 to the dialed number at the location manager 31.

Upon receipt of invite request 91, the location manager 31 queries the service control entity 29 with routing request 93. The service control entity 29 performs a data lookup and responds to the location manager 31 with a routing response 95. The location manager 31 determines that the call should be routed to the called party at the egress IP telephony gateway 21b and sends a SIP 305 temporarily moved response 97 back to the H.323 gatekeeper 25. The H.323 gatekeeper 25 sends a SIP invite request 99 to the called party at

the egress IP telephony gateway 21b. Upon receipt of the SIP invite request 99, the egress IP telephony gateway 21b sends a setup message 101 to the PBX 19b. When the PBX 19b rings the line of the called party, the PBX 19b sends an alerting message 103 back to the egress IP telephony gateway 21b. The egress IP telephony gateway 21b then sends a SIP 180 ringing message 105 back to the H.323 gatekeeper 25, which in turn sends a H.323 alerting message 107 to the ingress IP telephony gateway 21a. The ingress IP telephony gateway 21a then sends an alerting message 109 to PBX 19a, which provides a ringing tone to the calling party. When the called party answers, the PBX 19b sends a connect message 111 to the egress IP telephony gateway 21b. The egress IP telephony gateway 21b in turn sends a SIP 200 OK response 113 to the H.323 gatekeeper 25. The H.323 gatekeeper 25 sends an H.323 connect message 115 to the ingress IP telephony gateway 21a and a SIP ACK request 116 back to the egress IP telephony gateway 21b. Upon receipt of the message 115, the ingress IP telephony gateway 21a sends a connect message 117 to the PBX 19a and the VNET session is established.

At the conclusion of the VNET session, the called party hangs up and the PBX 19b sends a release message 119 to gateway 21b. Gateway 21b maps release 119 into a SIP BYE request 121 addressed to the calling party at the H.323 gatekeeper 25. The H.323 gatekeeper 25 then sends an H.323 release message 123 to the calling party at the ingress IP telephony gateway 21a and a SIP ACK request 124 back to the egress IP telephony gateway 21b. The ingress IP telephony gateway 21a sends a release message 125 to the PBX 19a to terminate the call. According to the H.323 protocol, at the conclusion of the session, the H.323 gatekeeper 25 sends a disengage request 127 to the ingress IP telephony gateway 21a, which responds with a disengage confirm 129. Then the H.323 gatekeeper 25 sends an end session command 131 to the ingress IP telephony gateway 21a, which responds with an end session command ACK 133. The H.323 gatekeeper 25 then sends a session detail record 135 to the appropriate billing authority.

From the foregoing, it may be seen that the present invention provides a method and system for providing intelligent network services in an IP telephony system. The location manager of the present invention functions as a SIP redirect server to provide signaling routing information to proxy servers. Those skilled in the art will recognize alternative
5 embodiments given the benefit of the foregoing disclosure. Accordingly, the foregoing is intended for purposes of illustration and not of limitation.

WHAT IS CLAIMED IS:

- 1 1. An IP telephony system, which comprises:
2 a location manger, the location manager including an interface to a legacy telephony
3 service control entity; and,
4 an IP telephony proxy server, the IP telephony proxy server including an IP interface
5 to the location manger.
- 1 2. The IP telephony system as claimed in claim 1, wherein the location manager
2 comprises means for requesting subscriber data from the legacy telephony service control
3 entity.
- 1 3. The IP telephony system as claimed in claim 1, wherein the location manager
2 comprises means for requesting intelligent network service information from the legacy
3 telephony service control entity.
- 1 4. The IP telephony system as claimed in claim 3, wherein the means for requesting
2 intelligent network service information comprises means for mapping a call control request
3 received from the IP telephony proxy server to a service control query to the legacy
4 telephony service control entity.
5
- 1 5. The IP telephony system as claimed in claim 1, wherein the location manager
2 comprises means for providing intelligent network service information to the IP telephony
3 proxy server

1 6. The IP telephony system as claimed in claim 5, wherein the means for providing
2 intelligent network service information comprises means for mapping intelligent network
3 service information to an IP address.

1

1 7. The IP telephony system as claimed in claim 5, wherein the means for providing
2 intelligent network service information comprises means for mapping service control
3 information received from the legacy telephony service control entity to an IP address.

1

1 8. The IP telephony system as claimed in claim 1, wherein the IP telephony proxy server
2 comprises means for processing IP telephony session control messaging.

1

1 9. The IP telephony system as claimed in claim 8, wherein the means for processing IP
2 telephony session control messaging comprises means for determining if intelligent network
3 service control is needed to initiate a session.

1

1 10. The IP telephony system as claimed in claim 9, wherein the means for processing IP
2 telephony session control messaging comprises means for sending an IP telephony session
3 control message to the location manager if intelligent network service control is needed to
4 initiate the session.

1

1 11. The IP telephony system as claimed in claim 10, wherein the location manager
2 comprises means for mapping IP telephony session control messages received from the IP
3 telephony proxy server to legacy telephony service control entity queries.

1

1 12. The IP telephony system as claimed in claim 11, where in the location manager
2 comprises means for mapping legacy telephony service control entity query responses to IP
3 telephony session control messages.

1

1 13. The IP telephony system as claimed in claim 8, wherein the means for processing IP
2 telephony session control messaging comprises means for bi-directionally translating session
3 control messaging from a first protocol to a second protocol.

1

1 14. The IP telephony system as claimed in claim 13, wherein one of the protocols is
2 H.323 and the other of the protocols is Session Initiation Protocol (SIP).

1

1 15. The IP telephony system as claimed in claim 1, wherein the location manager
2 comprises means for processing IP telephony service control messaging.

1

1 16. The IP telephony system as claimed in claim 15, wherein the means for processing IP
2 telephony service control messaging comprises means to mapping IP telephony session
3 control messages to legacy telephony service control entity queries.

1

1 17. The IP telephony system as claimed in claim 15, wherein the means for processing IP
2 telephony service control messaging comprises means to mapping legacy telephony service
3 control entity query responses to IP telephony session control messages.

1

1 18. The IP telephony system as claimed in claim 1, wherein the IP telephony proxy server
2 comprises an H.323 gatekeeper.

1

1 19. The IP telephony system as claimed in claim 1, wherein the IP telephony proxy server
2 comprises a Session Initiation Protocol proxy server.

1

1 20. A method of providing IP telephony services comprising the steps of:
2 receiving an IP telephony session initiation request to a called party at an IP telephony
3 proxy server;
4 determining if intelligent network service information is necessary to initiate the IP
5 telephony session; and
6 if intelligent network service information is necessary, sending an IP telephony
7 session initiation request to the called party at a location manager.

1

1 21. The method as claimed in claim 20, comprising the step of sending an intelligent
2 network service control query to a legacy telephony service control entity in response to
3 receiving the IP telephony session initiation request at the location manager.

1

1 22. The method as claimed in claim 21, comprising the step of sending an IP session
2 control message to the IP telephony proxy server in response to receiving a response to the
3 intelligent network service control query.

1

1/3




FIG. 1




FIG. 2

3/3




FIG. 3

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US00/26228

A. CLASSIFICATION OF SUBJECT MATTER

IPC(7) : H04M 07/00

US CL : 379/220

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 379/220; 370/352; 455/414;

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EAST

search terms: IP telephony, proxy server, mapping

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 6,161,008 A (LEE et al) 12 December 1998, col. 3, lines 53-62, Fig. 1.	1-22
A	US 6,141,341 A (JONES et al) 31 October 1998, col. 1-2, lines 64-8, Fig. 5.	1-22
A	US 5,329,578 A (BRENNAN et al) 12 July 1994, col. 3-4, lines 54-18, Fig. 2a.	1-22
A	US 5,563,938 A (SOSHEA et al) 08 October 1996, col. 4, lines 7-18.	1-22

☐ Further documents are listed in the continuation of Box C. ☐ See patent family annex.

* Special categories of cited documents:	*T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
A document defining the general state of the art which is not considered to be of particular relevance	*X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
E earlier document published on or after the international filing date	*Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	*G* document member of the same patent family
O document referring to an oral disclosure, use, exhibition or other means	
P document published prior to the international filing date but later than the priority date claimed	

Date of the actual completion of the international search

22 JANUARY 2001

Date of mailing of the international search report

21 MAR 2001

Name and mailing address of the ISA/US
Commissioner of Patents and Trademarks
Box PCT
Washington, D.C. 20231

Facsimile No. (703) 305-3230

Authorized officer

AHMAD MATAR

Telephone No. (703) 305-4700